

PATENT

Serial No.: 10/625,402

Docket No. 33565.2

Customer No. 000027683

Listing of Claims

The following listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Currently amended) A network device, comprising:

a housing;

circuitry within the housing for operating as a router to direct-multiplexing a communication of information between any of first, second and third communication devices via at least a wireless medium, wherein the circuitry includes a first connection for connecting to the first communication device, a second connection for connecting to the second communication device, a third connection for connecting to the third communication device, and a power connection for connecting the circuitry to an alternating current power source, and wherein the first, second and third communication devices are external to the housing;

a group of electrical prongs, mounted to the housing, for insertion into at least one primary receptacle of the alternating current power source, and for mechanically supporting at least a portion of the housing's weight when the group of electrical prongs is so inserted, wherein at least a portion of the group of electrical prongs is connected to the power connection for connecting the circuitry to the alternating current power source via the power connection and the group of electrical prongs when the group of electrical prongs is so inserted;

a first extension receptacle, mounted to the housing and connected to the group of electrical prongs, into which a first plug of a first extension device is insertable, for connecting the first extension device to the alternating current power source via the first plug and the group of electrical prongs when the first plug and the group of electrical prongs are so inserted; and

a second extension receptacle, mounted to the housing and connected to the group of electrical prongs, into which a second plug of a second extension device is insertable, for connecting the second extension device to the alternating current power source via the

PATENT
Serial No.: 10/625,402
Docket No. 33565.2
Customer No. 000027683

second plug and the group of electrical prongs when the second plug and the group of electrical prongs are so inserted.

2. (Previously presented) The network device of Claim 1, wherein the circuitry includes a power conditioning module for conditioning power from the alternating current power source, and wherein:

the power connection is for connecting the circuitry to the alternating current power source via the power connection, the power conditioning module, and the group of electrical prongs when the group of electrical prongs is so inserted;

the first extension receptacle is for connecting the first extension device to the alternating current power source via the first plug, the power conditioning module, and the group of electrical prongs when the first plug and the group of electrical prongs are so inserted; and

the second extension receptacle is for connecting the second extension device to the alternating current power source via the second plug, the power conditioning module, and the group of electrical prongs when the second plug and the group of electrical prongs are so inserted.

3. (Previously presented) The network device of Claim 1, wherein the circuitry includes a surge protection module for protecting the circuitry against a surge in power from the alternating current power source, and wherein:

the power connection is for connecting the circuitry to the alternating current power source via the power connection, the surge protection module, and the group of electrical prongs when the group of electrical prongs is so inserted;

the first extension receptacle is for connecting the first extension device to the alternating current power source via the first plug, the surge protection module, and the group of electrical prongs when the first plug and the group of electrical prongs are so inserted; and

the second extension receptacle is for connecting the second extension device to the alternating current power source via the second plug, the surge protection module, and the group of electrical prongs when the second plug and the group of electrical prongs are so

PATENT

Serial No.: 10/625,402

Docket No. 33565.2

Customer No. 000027683

inserted.

4. (Previously presented) The network device of Claim 1, wherein the group of electrical prongs includes:

a first group of electrical prongs, mounted to the housing, for insertion into a first primary receptacle of the alternating current power source, and for mechanically supporting at least a portion of the housing's weight when the first group of electrical prongs is so inserted, wherein the first group of electrical prongs is connected to the power connection for connecting the circuitry to the alternating current power source via the power connection and the first group of electrical prongs when the first group of electrical prongs is so inserted, wherein the first extension receptacle is connected to the first group of electrical prongs for connecting the first extension device to the alternating current power source via the first plug and the first group of electrical prongs when the first plug and the first group of electrical prongs are so inserted; and

a second group of electrical prongs, mounted to the housing, for insertion into a second primary receptacle of the alternating current power source, and for mechanically supporting at least a portion of the housing's weight when the second group of electrical prongs is so inserted, wherein the second extension receptacle is connected to the second group of electrical prongs for connecting the second extension device to the alternating current power source via the second plug and the second group of electrical prongs when the second plug and the second group of electrical prongs are so inserted.

5. (Previously presented) The network device of Claim 4, wherein the circuitry includes a power conditioning module for conditioning power from the alternating current power source, and wherein:

the power connection is for connecting the circuitry to the alternating current power source via the power connection, the power conditioning module, and the first group of electrical prongs when the first group of electrical prongs is so inserted;

the first extension receptacle is for connecting the first extension device to the alternating current power source via the first plug, the power conditioning module, and the

PATENT

Serial No.: 10/625,402

Docket No. 33565.2

Customer No. 000027683

first group of electrical prongs when the first plug and the first group of electrical prongs are so inserted; and

the second extension receptacle is for connecting the second extension device to the alternating current power source via the second plug, the power conditioning module, and the second group of electrical prongs when the second plug and the second group of electrical prongs are so inserted.

6. (Previously presented) The network device of Claim 4, wherein the circuitry includes a surge protection module for protecting the circuitry against a surge in power from the alternating current power source, and wherein:

the power connection is for connecting the circuitry to the alternating current power source via the power connection, the surge protection module, and the first group of electrical prongs when the first group of electrical prongs is so inserted;

the first extension receptacle is for connecting the first extension device to the alternating current power source via the first plug, the surge protection module, and the first group of electrical prongs when the first plug and the first group of electrical prongs are so inserted; and

the second extension receptacle is for connecting the second extension device to the alternating current power source via the second plug, the surge protection module, and the second group of electrical prongs when the second plug and the second group of electrical prongs are so inserted.

7. (Previously presented) The network device of Claim 1, wherein the circuitry is remotely controllable by the first communication device.

8. (Currently amended) The network device of Claim 1, wherein the first, second and third connections achieve redundancy for fault-tolerant operation of the communication of information between the first, second and third communication devices ~~is for connecting to the second communication device via a wireless medium.~~

PATENT

Serial No.: 10/625,402

Docket No. 33565.2

Customer No. 000027683

9. (Currently amended) The network device of Claim 1 ~~Claim 8~~, wherein the circuitry includes:
- circuitry for selecting a manner of communicating the information between the second connection and the second communication device via the wireless medium, including at least one of the following: wireless communication standard selection, mode selection, and channel selection.
10. (Previously presented) The network device of Claim 9, wherein the circuitry is remotely controllable by the first communication device.
11. (Previously presented) The network device of Claim 1, wherein the circuitry is mounted to the housing, and wherein the group of electrical prongs is mounted to the housing by mounting to the circuitry.
12. (Previously presented) The network device of Claim 1, wherein the second communication device is the first extension device.
13. (Previously presented) The network device of Claim 1, wherein the primary receptacle has a connector type, and wherein the first extension receptacle has the connector type.
14. (Previously presented) The network device of Claim 1, wherein the primary receptacle is mounted within a wall and is exposed to an outer surface of the wall, and comprising:
- a structure for securing the housing to the wall when the group of electrical prongs is so inserted.
15. (Previously presented) The network device of Claim 14, wherein the structure includes a screw for securing the housing to the wall.

PATENT

Serial No.: 10/625,402

Docket No. 33565.2

Customer No. 000027683

16. (Previously presented) The network device of Claim 14, wherein the structure includes a locking device for selectively preventing detachment of the housing from the wall.

17. (Previously presented) The network device of Claim 16, wherein the structure includes a screw for securing the housing to the wall, and wherein the locking device includes a cover for selectively preventing access to the screw.

18. (Previously presented) The network device of Claim 14, wherein the structure is for securing the housing to the wall by securing the housing to the receptacle.

19. (Currently amended) A network device, comprising:
a housing;

circuitry within the housing for operating as a router to direct a communication of communicating information between any of first and second communication devices via at least a wireless medium, wherein the circuitry includes a first connection for connecting to the first communication device, a second connection for connecting to the second communication device, and a power connection for connecting the circuitry to an alternating current power source;

a group of electrical prongs, mounted to the housing, for insertion into at least one primary receptacle of the alternating current power source, and for mechanically supporting at least a portion of the housing's weight when the group of electrical prongs is so inserted, wherein at least a portion of the group of electrical prongs is connected to the power connection for connecting the circuitry to the alternating current power source via the power connection and the group of electrical prongs when the group of electrical prongs is so inserted; and

an extension receptacle, mounted to the housing and connected to the group of electrical prongs, into which a plug of an extension device is insertable, for connecting the extension device to the alternating current power source via the plug and the group of electrical prongs when the plug and the group of electrical prongs are so inserted.

PATENT
Serial No.: 10/625,402
Docket No. 33565.2
Customer No. 000027683

20. (Previously presented) The network device of Claim 19, wherein the extension receptacle is a first extension receptacle, wherein the extension device is a first extension device, wherein the plug is a first plug of the first extension device, and comprising:

a second extension receptacle, mounted to the housing and connected to the group of electrical prongs, into which a second plug of a second extension device is insertable, for connecting the second extension device to the alternating current power source via the second plug and the group of electrical prongs when the second plug and the group of electrical prongs are so inserted.

21. (Previously presented) The network device of Claim 20, wherein the group of electrical prongs includes:

a first group of electrical prongs, mounted to the housing, for insertion into a first primary receptacle of the alternating current power source, and for mechanically supporting at least a portion of the housing's weight when the first group of electrical prongs is so inserted, wherein the first group of electrical prongs is connected to the power connection for connecting the circuitry to the alternating current power source via the power connection and the first group of electrical prongs when the first group of electrical prongs is so inserted, wherein the first extension receptacle is connected to the first group of electrical prongs for connecting the first extension device to the alternating current power source via the first plug and the first group of electrical prongs when the first plug and the first group of electrical prongs are so inserted; and

a second group of electrical prongs, mounted to the housing, for insertion into a second primary receptacle of the alternating current power source, and for mechanically supporting at least a portion of the housing's weight when the second group of electrical prongs is so inserted, wherein the second extension receptacle is connected to the second group of electrical prongs for connecting the second extension device to the alternating current power source via the second plug and the second group of electrical prongs when the second plug and the second group of electrical prongs are so inserted.

PATENT

Serial No.: 10/625,402

Docket No. 33565.2

Customer No. 000027683

22. (Previously presented) The network device of Claim 19, wherein the circuitry includes a power conditioning module for conditioning power from the alternating current power source, and wherein:

the power connection is for connecting the circuitry to the alternating current power source via the power connection, the power conditioning module, and the group of electrical prongs when the group of electrical prongs is so inserted; and

the extension receptacle is for connecting the extension device to the alternating current power source via the plug, the power conditioning module, and the group of electrical prongs when the plug and the group of electrical prongs are so inserted.

23. (Previously presented) The network device of Claim 19, wherein the circuitry includes a surge protection module for protecting the circuitry against a surge in power from the alternating current power source, and wherein:

the power connection is for connecting the circuitry to the alternating current power source via the power connection, the surge protection module, and the group of electrical prongs when the group of electrical prongs is so inserted; and

the extension receptacle is for connecting the extension device to the alternating current power source via the plug, the surge protection module, and the group of electrical prongs when the plug and the group of electrical prongs are so inserted.

24. (Previously presented) The network device of Claim 19, wherein the circuitry is remotely controllable by the first communication device.

25. (Currently amended) The network device of Claim 19, wherein the first and second connections achieve redundancy for fault-tolerant operation of the communication of information between the first and second communication devices ~~is for connecting to the second communication device via a wireless medium.~~

PATENT
Serial No.: 10/625,402
Docket No. 33565.2
Customer No. 000027683

26. (Currently amended) The network device of Claim 19 ~~Claim 25~~, wherein the circuitry includes:

circuitry for selecting a manner of communicating the information between the second connection and the second communication device via the wireless medium, including at least one of the following: wireless communication standard selection, mode selection, and channel selection.

27. (Previously presented) The network device of Claim 26, wherein the circuitry is remotely controllable by the first communication device.

28. (Previously presented) The network device of Claim 19, wherein the circuitry is mounted to the housing, and wherein the group of electrical prongs is mounted to the housing by mounting to the circuitry.

29. (Previously presented) The network device of Claim 19, wherein the second communication device is the extension device.

30. (Previously presented) The network device of Claim 19, wherein the primary receptacle has a connector type, and wherein the extension receptacle has the connector type.

31. (Previously presented) The network device of Claim 19, wherein the primary receptacle is mounted within a wall and is exposed to an outer surface of the wall, and comprising:

a structure for securing the housing to the wall when the group of electrical prongs is so inserted.

32. (Previously presented) The network device of Claim 31, wherein the structure includes a screw for securing the housing to the wall.

PATENT

Serial No.: 10/625,402

Docket No. 33565.2

Customer No. 000027683

33. (Previously presented) The network device of Claim 31, wherein the structure includes a locking device for selectively preventing detachment of the housing from the wall.

34. (Previously presented) The network device of Claim 33, wherein the structure includes a screw for securing the housing to the wall, and wherein the locking device includes a cover for selectively preventing access to the screw.

35. (Previously presented) The network device of Claim 31, wherein the structure is for securing the housing to the wall by securing the housing to the receptacle.

36. (Previously presented) The network device of Claim 19, wherein the first and second communication devices are external to the housing.

37. (Currently amended) A network device, comprising:
a housing;

circuitry within the housing for operating as a router to direct a communication of communicating information between any of first and second communication devices via at least a wireless medium, wherein the circuitry includes a first connection for connecting to the first communication device ~~via a wire~~, a second connection for connecting to the second communication device, and a power connection for connecting the circuitry to an alternating current power source; and

a group of electrical prongs, mounted to the housing, for insertion into at least one receptacle of the alternating current power source, and for mechanically supporting at least a portion of the housing's weight when the group of electrical prongs is so inserted, wherein at least a portion of the group of electrical prongs is connected to the power connection for connecting the circuitry to the alternating current power source via the power connection and the group of electrical prongs when the group of electrical prongs is so inserted.

38. (Previously presented) The network device of Claim 37, wherein the circuitry is remotely controllable by the first communication device.

PATENT

Serial No.: 10/625,402

Docket No. 33565.2

Customer No. 000027683

39. (Currently amended) The network device of Claim 37, wherein the first and second connections achieve redundancy for fault-tolerant operation of the communication of information between the first and second communication devices-is-for-connecting-to-the second communication device via a wireless medium.

40. (Currently amended) The network device of Claim 37-Claim 39, wherein the circuitry includes:

circuitry for selecting a manner of communicating the information between the second connection and the second communication device via the wireless medium, including at least one of the following: wireless communication standard selection, mode selection, and channel selection.

41. (Previously presented) The network device of Claim 40, wherein the circuitry is remotely controllable by the first communication device.

42. (Previously presented) The network device of Claim 37, wherein the circuitry is mounted to the housing, and wherein the group of electrical prongs is mounted to the housing by mounting to the circuitry.

43. (Previously presented) The network device of Claim 37, wherein the primary receptacle is mounted within a wall and is exposed to an outer surface of the wall, and comprising:

a structure for securing the housing to the wall when the group of electrical prongs is so inserted.

44. (Previously presented) The network device of Claim 43, wherein the structure includes a screw for securing the housing to the wall.

PATENT

Serial No.: 10/625,402

Docket No. 33565.2

Customer No. 000027683

45. (Previously presented) The network device of Claim 43, wherein the structure includes a locking device for selectively preventing detachment of the housing from the wall.

46. (Previously presented) The network device of Claim 45, wherein the structure includes a screw for securing the housing to the wall, and wherein the locking device includes a cover for selectively preventing access to the screw.

47. (Previously presented) The network device of Claim 43, wherein the structure is for securing the housing to the wall by securing the housing to the receptacle.

48. (Previously presented) The network device of Claim 37, wherein the first and second communication devices are external to the housing.

49. (Previously presented) The network device of Claim 37, wherein the second connection is a parallel connection.

50. (Previously presented) The network device of Claim 37, wherein the second connection is a serial connection.

51. (Previously presented) The network device of Claim 50, wherein the serial connection is a universal serial bus ("USB") connection.

52. (Previously presented) The network device of Claim 37, wherein the wire is a first wire, and wherein the second connection is for connecting to the second communication device via a second wire.

53. (Previously presented) The network device of Claim 37, wherein the second connection is an Ethernet connection.

PATENT

Serial No.: 10/625,402

Docket No. 33565.2

Customer No. 000027683

54. (Previously presented) The network device of Claim 37, wherein the second connections is a connection to a wide area network.

55. (Previously presented) The network device of Claim 54, wherein the wide area network is a global computer network.

56. (Previously presented) The network device of Claim 37, wherein the second connections is a connection to a print device.

57. (Previously presented) The network device of Claim 56, wherein the connection to the print device is a connection to the print device via a print server.

58. (Previously presented) The network device of Claim 37, wherein the receptacle is a primary receptacle, and comprising:

an extension receptacle, mounted to the housing and connected to the group of electrical prongs, into which a plug of an extension device is insertable, for connecting the extension device to the alternating current power source via the plug and the group of electrical prongs when the plug and the group of electrical prongs are so inserted.